

UNIT I

INTRODUCTION TO REHABILITATION

REHABILITATION

Rehabilitation is a multi-disciplinary process aimed at enabling individuals with disabilities or health conditions to reach and maintain their **optimal physical, sensory, intellectual, psychological, and social functional levels**.

It seeks to help them **achieve independence**, improve **quality of life**, and allow **full participation** in society.

WHO definition:

“Rehabilitation is a set of measures that assist individuals who experience or are likely to experience disability to achieve and maintain optimal functioning in interaction with their environments.”

2. KEY TERMINOLOGIES

Impairment

- **Definition:** Any loss or abnormality of a body structure or physiological function (including mental functions).
- **Types:** Sensory (e.g., vision, hearing), motor (e.g., paralysis), cognitive (e.g., memory loss)

Example: Amputation of a leg, hearing loss.

Disability

- **Definition:** A limitation in performing everyday activities due to impairment.
- Disability focuses on **function loss** in personal and social life.

Example: A person with amputation cannot walk, affecting mobility.

Handicap (Now termed as Participation Restriction)

- **Definition:** A social disadvantage resulting from an impairment or disability.
- It reflects the **interaction between the individual and the environment**.

Example: A wheelchair user is unable to access a school building due to lack of ramps.

3. PRIMARY AND SECONDARY DISABILITIES

Primary Disability

- The **main or original condition** causing the limitation.
Example: Spinal cord injury resulting in paralysis.

Secondary Disability

- Occurs **as a result of the primary condition**, often preventable.
Examples:

- Bed sores due to prolonged immobility
- Muscle atrophy from disuse
- Depression from social isolation

4. ACTIVITIES OF DAILY LIVING (ADLs)

ADLs are everyday tasks necessary for basic functioning and independence.

Types:

a. Basic ADLs

- Bathing
- Dressing
- Eating
- Toileting
- Transferring (e.g., bed to chair)
- Grooming

b. Instrumental ADLs

- Cooking
- Cleaning
- Transportation
- Managing money
- Using a phone or medication

► Role of Rehabilitation:

- Assists individuals in **regaining independence**
- Teaches **alternative methods** or introduces **assistive devices** to perform ADLs

5. APPROPRIATE TECHNOLOGY

► Definition:

Use of **locally available, low-cost, user-friendly, and sustainable technology** for rehabilitation.

► Features:

- Affordable and maintainable
- Easy to use and repair

23BME13 - REHABILITATION ENGINEERING

SHORT NOTES

www.learnbiochem.in

- Adaptable to local environment

Category	Device/Tool	Purpose	Materials Used	Local Adaptability
Mobility Aids	Bamboo Crutches	Support for walking	Bamboo, rubber tips	Highly available, easy to craft
	Hand-pedaled Tricycle	Mobility for lower-limb disabled	Steel frame, bicycle parts	Locally made by welders or bike shops
	Wooden Walking Stick	Balance support	Wood	Easy to produce in rural areas
	PVC Walker Frame	Support for elderly or post-surgery patients	PVC pipes	Lightweight and repairable locally
	Foldable Wheelchair	Mobility and portability	Steel, rubber, cloth	Can be produced in local workshops
Prosthetics/Orthotics	Jaipur Foot	Prosthetic foot for amputees	Rubber, wood, leather	Made in Indian workshops; low cost
	Plastic Leg Braces (KAFO)	Support for polio/paralysis	PVC, Velcro, foam	Lightweight and easily repairable
	Leather Splints	Stabilization of limbs	Leather, metal strips	Made by local cobblers or orthotic centers
Communication Aids	Picture Communication Boards	For speech-impaired individuals	Cardboard, pictures	Handmade; requires basic art materials
	Low-cost AAC Devices	Alternate speech generation	Recycled electronics	Created by NGOs or tech students
	Sign Language Charts	Education for hearing-impaired	Paper/laminated sheets	Printed and distributed locally
Daily Living Aids	Modified Spoon with Thick Grip	Help grip in arthritis	Plastic, foam padding	Easily modifiable household tools
	Bucket Seat for Toileting	Support in squatting posture	Plastic bucket, metal frame	Recyclable materials and adaptable
	Long-handled Reacher	Pick objects without bending	Aluminum rod, rubber grip	Can be crafted by local artisans

23BME13 - REHABILITATION ENGINEERING**SHORT NOTES**www.learnbiochem.in

Category	Device/Tool	Purpose	Materials Used	Local Adaptability
Education Aids	Tactile Learning Charts	For blind students	Cardboard, thread, buttons	Low-cost DIY school tools
	Braille Slates	Writing aid for blind students	Aluminum, plastic	Distributed by disability centers
	Enlarged Print Books	For visually impaired students	Paper and ink	Printed with large fonts
Vision/Hearing Aids	White Cane	Navigation for blind individuals	Aluminum or PVC	Made locally with simple tools
	Pocket Hearing Amplifier	Hearing support in mild hearing loss	Circuit board, speaker	Can be developed by NGOs with electronics
	Spectacle-type Magnifier	Reading help for low vision	Lenses, plastic frames	Easily assembled in rural optical shops
Home Modifications	Cement/Brick Ramps	Wheelchair access to homes	Bricks, cement	Community-built and sustainable
	Wall-mounted Grab Bars	Bathroom safety	Iron rods or pipes	Made by local plumbers or welders
	Adjustable Cooking Platforms	Ease of cooking in wheelchair	Wooden/metal frame	Made by carpenters
Vocational Tools	Foot-powered Sewing Machine	Job tool for mobility-limited individuals	Metal frame, treadle	Local tailoring shops can modify
	Adapted Writing Boards	For one-handed individuals	Wooden board with clamps	Easy to build using school materials
	Low-cost Loom	Skill training for visually impaired	Wood, yarn, thread	Built by trainers in skill centers

► Significance:

- Increases access to rehabilitation
- Encourages **community ownership**
- Suitable for **rural and low-resource settings**

6. RESIDUAL FUNCTION

► **Definition:**

The **remaining or preserved ability** of a person despite having a disability or impairment.

► **Focus in Rehabilitation:**

- Identifying strengths
- Training to **maximize existing capabilities**
- Providing **assistive devices or modifications**

► **Example:**

- A person with one paralyzed hand learns to write with the other.

7. REHABILITATION PROCESS

Definition

Rehabilitation is the process of restoring or improving physical, mental, social, and vocational abilities of a person who has suffered illness, injury, or disability — enabling them to live as independently and productively as possible.

WHO Definition:

“Rehabilitation is a set of interventions designed to optimize functioning and reduce disability in individuals with health conditions in interaction with their environment.”

Goals:

- Prevent or limit the disabling effects of the condition
- Restore independence
- Improve quality of life
- Integrate individuals back into **family, work, and society**

Phases:

1. **Acute Phase** – Medical management and stabilization
2. **Subacute Phase** – Beginning therapy, preventing complications
3. **Chronic Phase** – Long-term rehabilitation, ADL training
4. **Maintenance Phase** – Vocational training, social integration

8. REHABILITATION TEAM – MEMBERS AND ROLES

Rehabilitation is **team-based** professionals and includes professionals from multiple fields:

Member	Role
Physiatrist	Medical leader, plans rehab program
Physiotherapist	Exercises for strength, coordination, mobility
Occupational Therapist	Improves ADLs, provides adaptive tools
Speech Therapist	Restores communication and swallowing
Psychologist	Treats anxiety, depression, coping issues
Social Worker	Links to community resources, support groups
Nurses	Monitor recovery, provide care and education
Orthotist/Prosthetist	Design and fit artificial limbs or braces
Vocational Counselor	Assists in job retraining and placement
Family & Caregivers	Emotional support, daily assistance

9. REHABILITATION CARE – NEED FOR PROPER DELIVERY OF REHABILITATION CARE

► Importance:

- Early rehab prevents complications (e.g., contractures, sores)
- Promotes better recovery and social reintegration
- Saves long-term health costs
- Empowers the person to live independently

► Challenges:

- Lack of trained staff in rural areas
- Expensive equipment
- Poor awareness among families
- Fragmented services without coordination

10. COMMUNITY-BASED REHABILITATION (CBR)

► Definition:

23BME13 - REHABILITATION ENGINEERING
SHORT NOTES
www.learnbiochem.in

CBR is a **community-driven strategy** to ensure **equal opportunities and participation** of people with disabilities using local resources.

CBR shifts focus from **hospital-based care** to **community-level empowerment**.

Objectives of CBR:

- Empower disabled persons and their families
- Increase community awareness
- Promote equal access to education, jobs, and services
- Encourage **inclusive development**

Components of CBR (CBR Matrix by WHO):

Area	Focus
Health	Early detection, treatment, rehab services
Education	Inclusive schools, vocational training
Livelihood	Self-employment, skill development
Social	Social inclusion, disability rights
Empowerment	Awareness, leadership, advocacy

CBR Stakeholders:

- Disabled persons and families
- NGOs and self-help groups
- Local health workers
- Panchayat and village committees
- Government departments

Advantages:

- Uses existing local structures
- Cost-effective and scalable
- Ensures **long-term sustainability**

- Builds awareness and reduces stigma

11. DIFFERENCES: INSTITUTIONAL REHABILITATION vs. COMMUNITY-BASED REHAB

Feature	Institutional	CBR
Location	Hospitals/centers	Community/home
Cost	High	Low
Focus	Medical treatment	Social and functional reintegration
Professionals	Specialists	Trained community workers, families
Sustainability	Depends on funding	Community-led

12. LEGAL & ETHICAL ASPECTS IN REHABILITATION

- Right to dignity and respect
- Equal opportunities in education and jobs
- Accessibility to public spaces
- Right to assistive technology
- No discrimination based on disability

UNIT II

ENGINEERING CONCEPTS IN SENSORY AUGMENTATION AND SUBSTITUTION

1. Sensory augmentation and substitution

Feature	Sensory Substitution	Sensory Augmentation
Definition	Replacing a lost or damaged sense with another	Enhancing or extending existing senses
Main Purpose	Compensate for a sensory deficit	Improve or add new sensory capabilities
Target Users	People with sensory impairments or disabilities	Both impaired and non-impaired (healthy) individuals
Example	Using sound to represent vision for blind people	Feeling magnetic north through a wearable device
Type of Input	Converts familiar stimuli to another intact sense	Introduces new types of sensory input or enhancements
Based on Natural Senses	Yes – just using them in a different way	Sometimes includes non-human capabilities
Technology Used	Braille, cochlear implants, sensory substitution devices	Smart wearables, sensory implants, augmented reality
Goal	Restore normal function	Achieve superhuman or expanded perception

Key Point:

- **Substitution = Replacement**
- **Augmentation = Addition or Enhancement**

Visual System – Overview

The **visual system** is the part of the nervous system that enables organisms to **see**. It processes light information and helps interpret objects, colours, movement, and depth in the environment.

Major Components of the Visual System

Structure	Function
------------------	-----------------


Structure	Function
Eye	Captures light and focuses images on the retina
Retina	Contains photoreceptors (rods & cones) that convert light into electrical signals
Optic Nerve	Transmits visual information from the retina to the brain
Optic Chiasma	Partial crossing of optic nerve fibers for binocular vision
Optic Tract	Carries signals from the optic chiasma to the brain
Lateral Geniculate Nucleus (LGN)	Relay station in the thalamus for visual information
Visual Cortex (Occipital Lobe)	Interprets visual signals into images, motion, color, etc.

Photoreceptors in the Retina

Type	Function
Rods	Work in low light , responsible for black & white vision
Cones	Work in bright light , responsible for color vision

Pathway of Visual Information

1. **Light enters** the eye through the **cornea** → lens → focused on the **retina**
2. **Photoreceptors (rods/cones)** convert light to **electrical impulses**
3. Impulses pass through **bipolar and ganglion cells**
4. **Optic nerve** → **Optic chiasma** (fibers cross) → **Optic tract**
5. Signals go to **LGN** of thalamus → **Visual cortex (V1)** in occipital lobe



Functions of the Visual System

- Detect **light intensity** and **color**
- Recognize **objects, shapes**, and **faces**
- Perceive **motion** and **depth**
- Coordinate **eye movements**
- Support **spatial orientation**

Visual augmentation

Visual Augmentation – Explained

Visual augmentation refers to the **enhancement of natural vision** using technology. It aims to **extend or improve** what the human eye can normally see.

Definition:

Visual augmentation is the use of **technological devices or systems** to **enhance** visual perception, enabling users to see **better, farther, in the dark**, or even **see things not normally visible**, like infrared or ultraviolet light.

Types of Visual Augmentation

Type	Description	Example
Low Vision Aids	Help people with partial vision see more clearly	Magnifiers, electronic glasses
Night Vision Devices	Enhance vision in low light or darkness	Infrared goggles used in military
Zoom & Macro Systems	Magnify distant or tiny objects	Telescopic contact lenses, surgical loupes
Augmented Reality (AR)	Overlay digital images/info onto the real world	Smart glasses (e.g., Microsoft HoloLens)
Multispectral Vision	Extend vision to IR or UV spectra	Sensors that detect thermal or chemical data
Bionic Eyes (Retinal Implants)	Restore limited vision in the blind	Argus II retinal prosthesis

Applications

- **Medical:** Helping people with visual impairments
- **Military & Law Enforcement:** Night vision, target tracking

- **Aviation & Driving:** HUDs (Heads-Up Displays)
- **Industry:** AR-based quality control or navigation
- **Research & Exploration:** Seeing radiation, chemical leaks, etc.

Key Technologies Involved

- Augmented Reality (AR)
- Smart Glasses and Contact Lenses
- Computer Vision and AI
- Retinal Implants and Brain-Machine Interfaces

Tactual Vision Substitution

Tactual vision substitution is a type of **sensory substitution** where **touch (tactile sense)** is used to **replace vision**. It allows blind or visually impaired individuals to perceive visual information through **tactile stimuli**.

Definition:

Tactual vision substitution is the process of converting **visual images** into **tactile sensations**, allowing a person to "see" using **touch**.

How It Works:

1. **Visual input** (from a camera or image) is captured.
2. The visual information is **translated into tactile patterns**.
3. These patterns are delivered to the **skin**, usually on the **back, fingers, or tongue**.
4. The brain learns to interpret these patterns as representing **shapes, locations, or movement** — similar to visual perception.

Key Devices & Examples:

Device	Function
TVSS (Tactile Vision Substitution System)	First system developed by Paul Bach-y-Rita; converts camera input to vibrations on the back or abdomen
Tongue Display Unit (TDU)	Sends electrical pulses to the tongue to represent visual scenes
BrainPort	Modern version of the TDU; helps blind people "see" through tongue stimulation

23BME13 - REHABILITATION ENGINEERING
SHORT NOTES
www.learnbiochem.in

Device	Function
Haptic Gloves or Vests	Represent spatial information through vibrations or pressure on the skin

Applications:

- Helping **blind individuals** read, navigate, and identify objects
- **Training spatial awareness** using tactile maps or feedback
- **Research on neuroplasticity** — how the brain adapts to new forms of input

Scientific Basis:

- Based on the brain's **plasticity**: the visual cortex can process tactile information if trained.
- "We see with our brain, not just our eyes" — (Paul Bach-y-Rita)

Auditory Vision Substitution

Auditory vision substitution is a type of **sensory substitution** where **sound (auditory sense)** is used to **replace vision**. It allows blind or visually impaired individuals to "see" by interpreting **sounds that represent visual information**.

Definition:

Auditory vision substitution is the process of converting **visual images** into **sound patterns**, enabling a person to perceive shapes, objects, and spatial layout using **hearing** instead of sight.

How It Works:

1. A **camera** captures a real-time image.
2. A **software system** translates visual features (shape, brightness, position) into **audio cues** (pitch, volume, stereo position).
3. The user **hears** these sounds through headphones and **learns** to interpret them as visual information.

Key Devices & Systems:

Device/System	Function
The vOICe (by Peter Meijer)	Converts images into soundscapes; pitch = height, time = horizontal position, loudness = brightness
EyeMusic	Converts colors into musical instruments and brightness into volume
PSVA (Prosthesis Substituting Vision by Audition)	Early auditory substitution prototype

23BME13 - REHABILITATION ENGINEERING
SHORT NOTES
www.learnbiochem.in

Device/System	Function
Sonic Eye, SoundVision	Translate depth or object edges into audio feedback

Applications:

- **Blind navigation:** Users can detect doors, obstacles, or people.
- **Object recognition:** Differentiating between shapes (e.g., a cup vs. a chair).
- **Reading or viewing scenes** through soundscapes.
- **Cognitive training** in spatial awareness and neuroplasticity.

Scientific Basis:

- Utilizes **neuroplasticity**: the brain can reorganize and assign **visual processing tasks** to the **auditory cortex** and **visual cortex** based on learned input.

Summary Table:

Feature	Auditory Vision Substitution
Input	Visual (camera/image)
Output	Sound patterns (auditory)
Used By	Blind or visually impaired
Sound Properties	Pitch, tone, stereo position, volume
Key Benefit	Allows "seeing by hearing"

Comparison (Tactual vs Auditory Vision Substitution):

Feature	Tactual Vision Substitution	Auditory Vision Substitution
Output Modality	Touch (skin, tongue, fingers)	Sound (ears, headphones)
Feedback Type	Vibration, pressure, electric pulses	Soundscape with pitch, volume
Learning Curve	Moderate	High (needs auditory interpretation)
Key Advantage	Intuitive, spatial mapping	Hands-free, full visual field

Auditory System

The **auditory system** is the sensory system responsible for **hearing**. It captures **sound waves**, converts them into **electrical signals**, and sends them to the **brain** for interpretation.

Main Functions:

- Detect **sound waves**
- Recognize **pitch**, **loudness**, and **direction**
- Interpret **speech**, **music**, and **environmental sounds**
- Aid in **balance** (via the inner ear)


Major Parts of the Auditory System

Part	Sub-Parts	Function
Outer Ear	- Pinna - Auditory canal	Captures sound and funnels it toward the eardrum
Middle Ear	- Tympanic membrane (eardrum) - Ossicles (malleus, incus, stapes)	Converts sound waves to mechanical vibrations
Inner Ear	- Cochlea - Vestibular system	Cochlea: converts vibrations into nerve signals Vestibular system: maintains balance
Auditory Nerve	- Cochlear nerve (part of CN VIII)	Transmits sound information to the brain
Brain Pathways	- Brainstem - Thalamus - Auditory cortex (Temporal lobe)	Processes and interprets sound

Pathway of Sound (Step-by-Step)

1. **Sound waves** enter the **pinna** and travel through the **auditory canal**.
2. Hit the **eardrum**, causing it to **vibrate**.
3. Vibrations pass through **ossicles** (malleus → incus → stapes).
4. Stapes presses against the **oval window** of the cochlea.
5. **Fluid in the cochlea** moves, stimulating **hair cells**.
6. Hair cells convert movement into **electrical impulses**.

7. Impulses travel via the **auditory nerve** to the **brainstem**, **thalamus**, then the **auditory cortex**.
8. Brain interprets the signal as **sound** (e.g., speech, music, noise).



Key Features of Hearing

Feature	Explanation
Frequency (Pitch)	High or low sound (measured in Hz)
Amplitude (Loudness)	Intensity of sound (measured in dB)
Localization	Ability to detect sound direction
Tonotopy	Different parts of cochlea respond to different frequencies

Auditory Augmentation

Auditory augmentation refers to **enhancing natural hearing abilities** using technology. Unlike auditory substitution (which replaces lost hearing), augmentation improves or extends what a normal ear can perceive.

Definition

23BME13 - REHABILITATION ENGINEERING
SHORT NOTES
www.learnbiochem.in

Auditory augmentation is the use of **technology to improve, amplify, or extend the auditory perception** beyond its natural range — either for medical, military, or general performance purposes.

Purpose of Auditory Augmentation

- Enhance **hearing sensitivity**
- Expand **frequency range** beyond human limits
- Improve **speech understanding** in noisy environments
- Add **non-auditory cues** (like alerts) via sound

Examples of Auditory Augmentation Technologies

Technology	Function
Hearing aids	Amplify sound for people with mild to moderate hearing loss
Cochlear implants (in augmented mode)	Directly stimulate the auditory nerve with enhanced processing
Directional microphones	Help focus on sound from one direction (like a conversation in noise)
Augmented reality earbuds	Overlay virtual audio with real-world sound (e.g., Google Pixel Buds, Apple AirPods Pro)
Bionic ears with extended frequency	Let users hear ultrasonic or subsonic sounds
AI-powered auditory filters	Reduce noise, highlight speech, or isolate specific sounds
Bone conduction devices	Transmit sound via skull bones, bypassing outer/middle ear
Military hearing enhancement systems	Enhance soft sounds while protecting against loud noises

Applications

- **Medical:** Enhanced hearing for individuals with hearing impairment
- **Military/Law Enforcement:** Situational awareness in noisy environments
- **Sports:** Athletes using earbuds to monitor biometrics or coach instructions
- **Everyday life:** Noise cancellation and enhanced audio in AR glasses or earbuds

Hearing Aids

Hearing aids are small electronic devices designed to **improve hearing** for people with **hearing loss** by **amplifying sound**. They make sounds **louder and clearer**, especially speech.

Definition:

A **hearing aid** is a battery-powered device worn in or behind the ear that **amplifies sound** and helps individuals with **partial hearing loss** to hear better.

Main Parts of a Hearing Aid

Component	Function
Microphone	Picks up sound from the environment
Amplifier	Increases the volume and clarity of the sound
Speaker (Receiver)	Sends the amplified sound into the ear
Battery	Powers the device
Processor (Digital chip)	Filters and adjusts sound (in digital hearing aids)

Types of Hearing Aids

Type	Placement	Features
Behind-the-Ear (BTE)	Rests behind the ear with a tube into the ear canal	Durable, suitable for all ages and hearing levels
In-the-Ear (ITE)	Fits completely inside the outer ear	Easier to handle, larger battery
In-the-Canal (ITC)	Fits partly in the ear canal	Smaller and more discreet
Completely-in-Canal (CIC)	Fits deeply inside the ear canal	Very discreet, may be harder to handle
Receiver-in-Canal (RIC)	Similar to BTE but speaker sits in canal	Better sound quality, smaller device

How Hearing Aids Work

1. **Microphone** picks up external sounds.
2. **Processor** analyzes and amplifies the sound.

3. **Amplifier** boosts the signal to the correct level.
4. **Speaker** sends the sound into the ear canal.
5. The **user hears** the amplified sound clearly.

Who Needs Hearing Aids?

- People with **sensorineural hearing loss** (due to damage to hair cells in the cochlea)
- Elderly individuals with **age-related hearing decline (presbycusis)**
- Individuals exposed to **loud noise** or **ototoxic drugs**

Advantages

- Improves **communication** and **quality of life**
- Reduces **social isolation**
- Some models include **Bluetooth**, **noise reduction**, and **directional microphones**

Limitations

- Not a cure for deafness
- Requires **adjustment and training**
- Needs **regular maintenance and batteries**

Cochlear Implants

A **cochlear implant** is a sophisticated electronic medical device that helps **restore hearing** for individuals with **severe to profound sensorineural hearing loss**, especially when hearing aids are no longer effective.

Definition:

A **cochlear implant** is a surgically implanted electronic device that **bypasses damaged parts of the inner ear** and directly **stimulates the auditory nerve**, allowing the person to **perceive sound**.

Components of a Cochlear Implant

Part	Location	Function
Microphone	External (behind the ear)	Picks up sound from the environment
Speech Processor	External	Converts sound into digital signals
Transmitter Coil	External (attached to head)	Sends digital signals through the skin to the internal receiver
Receiver/Stimulator	Internal (under skin behind ear)	Receives signals and sends them to the electrode
Electrode Array	Internal (inserted into cochlea)	Stimulates the auditory nerve fibers directly

How a Cochlear Implant Works

1. **Microphone** detects sound.
2. **Speech processor** converts sound into digital signals.
3. **Transmitter coil** sends signals through the skin to the **internal receiver**.
4. **Receiver** passes signals to the **electrode array** implanted in the cochlea.
5. **Electrodes** stimulate the **auditory nerve** directly.
6. Brain interprets these signals as **sound**.

Who Can Benefit?

- Children born deaf (after age 1 typically eligible)
- Adults who lost hearing later in life
- Individuals who receive **limited or no benefit from hearing aids**

Advantages

- Allows recognition of **environmental sounds and speech**
- Can support **language development in children**
- Improves **quality of life and social integration**

Limitations

- Requires **surgery**
- Sound perception is **not natural**; needs **training and adaptation**
- May not help with **speech understanding** in every case
- **Not suitable** for all types of deafness

Comparison: Cochlear Implant vs. Hearing Aid

Feature	Hearing Aid	Cochlear Implant
Use	Amplifies sound	Bypasses damaged ear and stimulates nerve directly
For	Mild to moderate hearing loss	Severe to profound hearing loss
Involves Surgery	No	Yes
Natural Hearing	Preserved (if present)	Requires brain adaptation

Visual-Auditory Substitution

Visual-auditory substitution is a type of **sensory substitution** where **auditory (hearing) input is used to replace visual information**, allowing blind individuals to "**see with their ears.**"

Definition:

Visual-auditory substitution refers to the **conversion of visual data** (such as shapes, colors, or movement) into **auditory signals**, so that people with vision loss can perceive the world using **sound**.

How It Works:

1. A **camera** captures the surrounding visual scene.
2. A **software algorithm** translates image features into sound patterns (pitch, tone, volume, spatial cues).
3. The user **wears headphones** and **learns** to interpret these soundscapes as visual information.

Key Devices & Systems

Device/System	Function
The vOICe (by Peter Meijer)	Translates camera input into complex soundscapes (e.g., pitch = height, time = horizontal location, volume = brightness)
EyeMusic	Converts colors into musical instruments and brightness into volume
SoundVision	Detects objects and their position using sound
PSVA (Prosthesis Substituting Vision by Audition)	Early device for converting vision to sound

Applications

- **Blind navigation:** Detect obstacles, recognize shapes and spaces.
- **Object recognition:** Identify household items or people.
- **Reading:** Some systems can convert printed text into musical tones or speech.
- **Spatial awareness training:** Helps users understand space and motion using sound.

Tactual-Auditory Substitution

Tactual-auditory substitution is a form of **sensory substitution** where **tactile (touch) input** is used to **replace or support hearing (auditory) perception**. It allows people who are **deaf or hard of hearing** to “hear” through touch.

Definition:

Tactual-auditory substitution is the process of **translating sound information** into **tactile (vibrational or pressure-based) stimuli**, enabling the brain to interpret **auditory cues** through the **sense of touch**.

How It Works:

1. **Microphone or sound sensor** captures environmental or speech sounds.
2. A **signal processor** converts these sounds into patterns (vibration, pressure, tapping).
3. These patterns are delivered to the **skin** (via wearable devices like gloves, vests, or wristbands).
4. The **user learns to interpret** these patterns as corresponding to specific sounds, speech, or alerts.

Devices and Technologies

Device/System	Function
Tactaid	Converts speech into vibratory patterns felt on the body
Vibrotactile vests/gloves	Deliver directional or frequency-based sound info via vibration
The Voice Jacket	Sends real-time speech vibrations to skin for deaf users
Bone conduction devices	Transmit sound through skull bones, merging touch and hearing

Applications

- **Deaf or hard of hearing individuals:** Alternative way to sense sound
- **Speech therapy:** Helps with **speech timing and rhythm** using vibration
- **Alerts and notifications:** Silent alarms for danger, phone calls, etc.
- **Multisensory rehabilitation:** Training the brain to process sound through other sensory input

Scientific Basis

- Relies on **neuroplasticity**: the brain can learn to interpret tactile input as meaningful sound (especially when auditory input is missing).
- Often, **auditory cortex** is activated by tactile stimuli in deaf users with proper training.

Benefits

Advantage	Explanation
Non-invasive	No surgery required, wearable devices only
Real-time	Immediate sound-to-touch conversion
Helps in noisy or silent environments	Useful where auditory aids fail
Supports communication	Helps recognize speech rhythm or alerts

Summary Table:

Feature	Tactual-Auditory Substitution
Input	Sound (speech, environment)
Output	Tactile signals (vibration, pressure)
Used by	Deaf, hard-of-hearing individuals
Goal	Substitute hearing through touch
Key Devices	Tactaid, vibrotactile gloves/vests

Tactual System

The **tactual (tactile) system** is responsible for processing **touch-based sensations** such as **pressure, vibration, texture, pain, and temperature**. It helps in object recognition, spatial awareness, and interaction with the environment.

Tactual System

1. Tactual Augmentation

Definition:

Tactual augmentation refers to **enhancing or extending the sense of touch** using technology to provide superhuman or additional tactile capabilities.

Examples:

- **Wearable haptic suits** for VR gaming that simulate touch, pain, or impact

- **Surgeons using haptic feedback tools** in robotic surgery
- **Enhanced prosthetic limbs** with pressure/vibration sensors
- **Smart gloves** that give feedback on grip force or object texture
- **Exoskeletons** that enhance strength and provide tactile feedback

Purpose:

- Improve **precision, awareness, or performance** in real or virtual tasks
- Used by healthy individuals in **training, medicine, or military**

Applications:

- Virtual reality (VR), telemedicine, robotics
- Training simulations, remote operations, space missions

2. Tactual Substitution

Definition:

Tactual substitution uses the **sense of touch to replace a missing or impaired sense**, such as vision or hearing.

Examples:

- **Braille**: Touch-based reading system for the blind
- **Tactile vision substitution systems (TVSS)**: Convert camera images to skin vibrations
- **Tactaid**: Converts speech sounds to vibrations for deaf users
- **BrainPort device**: Converts camera input into electrical pulses on the tongue

Purpose:

- Allow people with **sensory impairments** to interpret information using **touch**
- Example: “seeing” or “hearing” via vibrations or pressure

Applications:

- For the **blind or visually impaired** (visual-to-tactile)
- For the **deaf** (auditory-to-tactile)
- Used in **special education, rehabilitation, and assistive technology**

Summary Comparison

Feature	Tactual Augmentation	Tactual Substitution
Purpose	Enhance normal tactile function	Replace lost sense using touch

23BME13 - REHABILITATION ENGINEERING

SHORT NOTES

www.learnbiochem.in

Feature	Tactual Augmentation	Tactual Substitution
User	Mostly healthy individuals	People with sensory impairments
Example Devices	Haptic gloves, smart prosthetics, VR suits	Braille, TVSS, BrainPort, Tactaid
Sensory Pathway Used	Natural tactile pathways with enhancement	Tactile pathway substitutes vision/hearing
Field of Use	Medicine, military, gaming, robotics	Rehabilitation, education, assistive tech

Unit III

Orthopedic prosthetics and orthotics

Engineering Concepts in Motor Rehabilitation

Motor rehabilitation aims to restore movement and function after injury, disease, or disability. Engineering plays a key role by developing technologies and tools to support this process. Below are the core engineering concepts applied in motor rehabilitation:

1. Biomechanics

- Definition: Study of forces acting on the human body and the mechanics of body movement.
- Application: Understanding joint kinematics, muscle forces, gait analysis.
- Use: Design of prosthetics, orthotics, and assistive devices tailored to human movement.

2. Kinematics and Kinetics

- Kinematics: Studies motion without considering forces (e.g., joint angles, velocity).
- Kinetics: Analyzes forces that cause motion (e.g., torque, ground reaction forces).
- Application: Used in gait training, motion analysis systems, and robotic devices.

3. Ergonomics and Human Factors Engineering

- Definition: Designing devices and environments to fit the human body's capabilities and limitations.
- Application: User-friendly interfaces in assistive technology; minimizing strain or risk of injury.

4. Robotics and Mechatronics

- Robotics: Used to build intelligent rehabilitation devices like exoskeletons.
- Mechatronics: Integration of mechanical, electronic, and computer systems.
- Examples:
 - Robotic gait trainers (e.g., Lokomat)
 - Myoelectric prosthetic arms
 - Hand rehabilitation robots

5. Control Systems Engineering

- Definition: Designing systems that can monitor, adjust, and automate movement.
- Application: Closed-loop systems in exoskeletons and FES (Functional Electrical Stimulation) systems.
- Examples: PID controllers in robotic arms, feedback systems for muscle stimulation.

6. Sensor Technology

- Types: EMG sensors, pressure sensors, inertial measurement units (IMUs), force sensors.
- Use: Detect muscle activity, joint angles, limb positions.
- Application: Used in prosthetics, biofeedback systems, motion tracking.

7. Signal Processing

- Purpose: To analyze bio-signals like EMG, EEG for motor intention detection.
- Application:
 - Myoelectric control of prosthetics
 - Brain-Computer Interface (BCI)-controlled rehabilitation

8. Material Science

- Application: Development of lightweight, durable, and biocompatible materials for prosthetics and orthotics.
- Materials: Carbon fiber, thermoplastics, silicone, titanium.

9. Artificial Intelligence and Machine Learning

- Use: Adaptive learning systems that personalize rehabilitation based on patient performance.
- Application:
 - Predictive models for therapy outcomes
 - Intelligent prosthetic control
 - Motion pattern recognition

10. Virtual Reality (VR) and Augmented Reality (AR)

- VR: Immersive environments for task-specific motor training.
- AR: Overlaying digital cues onto the real world to guide movement.
- Benefits: Engaging, motivational, and adaptable for different rehabilitation tasks.

Artificial Limbs (Prosthetics)

Artificial limbs, also known as **prostheses**, are mechanical devices that replace missing limbs and aim to restore function and appearance. They are crucial in motor rehabilitation for individuals who have undergone amputation due to trauma, disease, or congenital conditions.

Types of Artificial Limbs

1. Upper Limb Prosthetics

- **Transradial (Below-elbow)**: Replaces arm below the elbow.
- **Transhumeral (Above-elbow)**: Replaces arm above the elbow.
- **Shoulder disarticulation**: Entire arm is replaced.

2. Lower Limb Prosthetics

- **Transtibial (Below-knee):** Replaces leg below the knee.
- **Transfemoral (Above-knee):** Replaces leg above the knee.
- **Hip disarticulation:** Replaces entire leg.

Components of an Artificial Limb

Part	Function
Socket	Custom-fit interface that connects the limb stump to the prosthesis.
Suspension	Holds the prosthesis onto the limb (e.g., suction, straps).
Pylon	Provides structural support (often made of metal/carbon fiber).
Terminal Device	The working end of the prosthesis (e.g., hand, hook, foot).
Joints	Mimic elbow, knee, or ankle motion depending on level.

Types of Control Mechanisms

1. Body-Powered Prosthetics

- Uses cables and harnesses driven by shoulder or upper body motion.
- **Advantages:** Lightweight, durable, low cost.
- **Limitations:** Limited functionality, not cosmetically appealing.

2. Externally Powered Prosthetics

- Controlled by electric motors using external power sources (battery).
- Often use **myoelectric control** – signals from residual muscles trigger movement.
- **Advantages:** More natural, improved control, cosmetic.
- **Limitations:** Expensive, requires maintenance and training.

3. Hybrid Prosthetics

- Combines body-powered and myoelectric systems.
- Example: Elbow is body-powered, hand is myoelectric.

Controlled Orthotics and Prosthetics

Controlled orthotics and prosthetics refer to **intelligent assistive devices** that support, enhance, or replace limb function using **external control mechanisms** like motors, sensors, and microprocessors.

1. Controlled Orthotics

Orthotics are external devices designed to **support or correct** musculoskeletal deformities or neuromuscular deficits **without replacing a limb**.

Examples of Controlled Orthotic Devices:

a. Powered Exoskeletons

- Assist movement in patients with spinal cord injury or stroke.
- Equipped with **motors, sensors, and controllers**.
- Example: **ReWalk, Ekso Bionics**

b. Functional Electrical Stimulation (FES) Orthosis

- Uses **electrical pulses** to stimulate paralyzed muscles.
- Helps in walking or arm movement by controlled stimulation.
- Example: Parastep system

c. Microprocessor-Controlled Orthotic Knees (MPK)

- Adjusts knee resistance in real-time during gait.
- Improves stability, especially on stairs or uneven ground.
- Example: **C-Brace by Ottobock**

2. Controlled Prosthetics

Prosthetics are devices that **replace** a missing limb or body part. Controlled prosthetics go beyond basic mechanical designs by using **electronic or neural signals**.

Control Methods:

a. Myoelectric Control

- Electrodes detect EMG signals from residual muscles.
- Signals control motorized movement of prosthetic joints.
- Example: **i-Limb, Bebionic Hand**

b. Microprocessor-Controlled Prosthetic Knees

- Embedded sensors and algorithms adjust the knee during walking.
- Provide natural gait and reduce energy expenditure.
- Example: **Genium, Rheo Knee**

c. Targeted Muscle Reinnervation (TMR)

- Surgery reroutes nerves from the amputated limb to other muscles.
- Allows **more intuitive control** of prosthetics.
- Example: DEKA "LUKE" Arm.

d. Brain-Computer Interface (BCI) Prosthetics (*experimental*)

- Brain signals decoded to control robotic limbs.
- Still in clinical research; future of prosthetic control.